

SAFETY DATA SHEET

BOND-X HD CARPET ADHESIVE AEROSOL 500ml

SECTION 1; IDENTIFICATION OF THE SUBSTANCES/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name bond-X
Product No. ADH8500

1.2. Relevant identified uses of the substances or mixture and uses advised against

Identified uses Spray adhesive

1.3. Details of the supplier of the data sheet
Supplier bond-X Ltd

Email info@bond-x.uk

SECTION 2; HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (EC 1272/2008) Physical and chemical hazards Extremely Flam. Aerosol - H222;H229

Human health Carc.2 – H351

Skin. Irrit. 2 – H315 Eye Irrit. 2 – H319 STOT SE 3 – H336

Environment Not Classified

The full text for all Hazard statements are displayed in Section 16.

2.2 Label Elements

Contains DICHLOROMETHANE

METHYL ETHYL KETONE

Label in Accordance with (EC) No. 1272/2008



Danger

Hazard statements

Signal word

H222 Extremely flammable aerosol.

bond-X Ltd		REV 5.0	JULY 2024
	H351	Suspected of causing cancer	
	H315	Causes skin irritation.	
	H319	Causes serious eye irritation.	
	H229	Pressurized container; may burst if heated	
	H336	May cause drowsiness or dizziness	
Precautionary Stateme	ents		
	P102	Keep out of reach of children	
	P210	Keep away from heat, hot surfaces, sparks, flam	es and
		other ignition sources. No smoking.	
	P211	Do not spray on an open flame or other ignition	source.
	P251	Do not pierce or burn, even after use.	
	P261	Avoid breathing dust/fume/gas/mist/vapours/sp	ray.
	P271	Use only outdoors or in a well ventilated area.	
	P280	Wear protective gloves/protective clothing/eye	
		4protection/ face protection.	
Supplementary precau	itionary stateme	nts	
	P302 + P352	IF ON SKIN: Wash with plenty of soap and water	
	P304+P340	IF INHALED: Remove victim to fresh air and keep rest in position comfortable for breathing.	at
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and ot do. Continue Rinsing.	
	P308+313	If exposed or concerned: Get medical advice/att	ention
	P410+412	Protect from sunlight. Do not expose to temperate exceeding 50°C/122°F.	
	P501	Dispose of contents/container in accordance wit Local Regulations.	h

2.3. Other hazards

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent material – NO SMOKING.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

PETROLEUM GASES LIQUIFIED		30-50%
CAS- No.: 68476-85-7	EC No.: 270-704-2	
Classification (EC 1272/2008)		
Flam. Gas 1- H220		

DICHLOROMETHANE		30-60%
CAS-No.: 75-09-2	EC No.: 200-838-9	
Classification (EC 1272/2008)		
Carc.Cat 2 – H351		
Skin Irrit Cat 2 – H315		
Eye Irrit Cat 2 – H319		
STOT SE Cat 3 – H336		

METHL ETHYL KETONE		1-<2.0%
CAS-No.: 78-95-3	EC No.: 201-159-0	
Classification (EC 1272/2008)		

Carc.Cat 2 – H351 Skin Irrit Cat 2 – H315 Eye Irrit Cat 2 – H319 STOT SE Cat 3 – H336

The full text for all R-Phrases and hazard statements are displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately

Skin contact

Wash the skin immediately with soap and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if any discomfort continues.

Eve Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling section 2.2, and/or in section 11.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Extinguishing media

Fire can be extinguished using: foam; carbon dioxide; dry powder

5.2 Special hazards arising from the substance or mixture

Unusual fire & Explosion hazards

Canisters may explode in fire.

Toxic gases/vapours/fumes of: Carbon Dioxide (CO₂). Carbon Monoxide (CO)

5.3 Advice for firefighters

Wear self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Avoid breathing vapours, mist or gas. Wear personal protective equipment (see section 8).

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environment Agency or other regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3 Methods and material for containment and cleaning up

Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth, and place into containers.

6.4 Reference to other sections

Wear protective clothing as described in section 8 of this safety data sheet. For waste disposal see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Must not be exposed to direct sunlight or temperatures above 50°C.

7.3 Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Name	STD	TWA - 8 H	Irs	STEL - 15	Min	Notes
DICHLOROMETHANE	WEL	100 ppm(Sk)	353 mg/m3(Sk)	200 ppm (Sk)	706 mg/m3 (Sk)	IRELAND TWA:50ppm TWA:174 mg/m3 STEL:150ppm STEL:552 mg/m3
PETROLEUM GASES LIQUIFIED	WEL	1000 ppm (Sk)	1250 mg/m3(Sk)	1250 ppm(Sk)	2180 mg/m3(Sk)	IRELAND TWA:500ppm TWA:625mg/m3 STEL:625ppm STEL:1090mg/m3
METHYL ETHYL KETONE	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	900 mg/m3 (Sk	IRELAND TWA:3ppm TWA:10mg/m3 STEL:10ppm STEL:33mg/m3

WEL = Workplace exposure limit.

Derived No Effect Level (DNEL).

Methylene Chloride (75-09-2)

Type	Exposure Route	Derived No effect Level	Safety Factor
Worker	Inhalation	706 mg/kg bw/d	
Short Term			
Systemic health effects			
Worker	Dermal	4750 mg/m ³	
Long Term			
Systemic Health effects			
Worker	Inhalation	353 mg/m ³	
Long Term			
Systemic health effects			

Methyl ethyl Ketone (78-92-3)

Туре	Exposure Route	Derived No effect Level	Safety Factor
Worker	Dermal	1161 mg/m³	
Long Term			
Systemic Health effects			
Worker	Inhalation	600 mg/kg bw/d	
Long Term			
Systemic Health effects			

Methylene Chloride (75-09-2)

Туре	Exposure Route	Derived No effect Level	Safety Factor
Consumer	Inhalation	353 mg/m ³	
Short Term			
Systemic health effects			
Consumer	Dermal	2395 mg/kg bw/d	
Long Term			
Systemic health effects			

DOTIG A LLG	ILLV J	.0	JOL1 2027
Consumer	Oral	0.06 mg/kg bw/d	
Long Term			
Systemic health effects			
Consumer	Inhalation	88.3 /m³	
Long Term			
Systemic health effects			

Methyl ethyl Ketone (78-92-3)

Type	Exposure Route	Derived No effect Level	Safety Factor
Consumer	Dermal	412 mg/kg bw/d	
Long Term			
Systemic health effects			
Consumer	Inhalation	106 mg/kg bw/d	
Long Term			
Systemic health effects			
Consumer	Oral	31 mg/m³	
Long Term			
Systemic health effects			

Predicted No effect Concentration (PNEC)

Methylene Chloride (75-09-2)

Environmental Compartment	Predicted No effect Concentration (PNEC)
Freshwater	0.54 mg/l
Freshwater - intermittent	4.47 mg/l
Marine water	0.194 mg/l
Marine sediment	1.61 mg/l
Soil	0.583mg/kg dry weight

Methyl ethyl Ketone (78-92-3)

	
Environmental Compartment	Predicted No effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater - intermittent	287.74mg/l
Marine sediment	287.7mg/l
Soil	22.5 mg/kg dry weight

8.2 Exposure controls

Protective equipment









Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eye/face protection

Chemical splash goggles or face shield. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).

Hand protection

Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Nitrile rubber.

Other skin and body protection

Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Wear protective clothing.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Use respirators and components tested and approved under appropriate government standards such as CEN (EU).

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

(a) Physical State Liquid

(b) Appearance Canister/Aerosol.(c) Colour Amber/Clear

(d) Odour Chlorinated hydrocarbon

(e) Odour Threshold
No data available
(f) Melting point/freezing point
No data available

(g) Initial boiling point and boiling range Not applicable - aerosol

(h) Flammability

Or explosive limits No data available

(j) Flash Point Not applicable – aerosol

(k) Auto-ignition temperature No data available

(I) Decomposition temperature Not applicable – insoluble in water

(m) pH as gaseous solution No data available (n) Kinematic Viscosity No data available (o) Dynamic Viscosity No data available (p) Water solubility No data available (q) Solubilities No data available (r) Partition coefficient No data available (s) Vapour pressure No data available (t) Relative density 1.2 (Adhesive only) No data available (u) Relative Vapour Density

(v) Particle characteristics

Particle Size No data available
Particle size distribution No data available

9.2 Other information

No data available

9.2.1 Information with regards to physical hazards classes

Not applicable

9.2.2 Other safety characteristics

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available.

10.2 Chemical stability

Avoid heat, sparks, and flames, stable under normal conditions.

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Avoid heat, flames and other sources or ignition. Avoid contact with: Strong oxidising agents, Strong alkalis and Strong mineral acids.

10.5 Incompatible materials

Materials to avoid

Strong acids, strong oxidising substances and strong alkalis.

10.6 Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO); Carbon Dioxide (CO2); Phosgene (COCl2); Hydrogen Chloride (HCl). Slow hydrolysis with water forms hydrochloric acid.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Methylene Chloride (75-09-2)

Acute toxicity

LD50 Oral - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Mouse - 4 h - 86 mg/l - vapor

Remarks: (ECHA)

Symptoms: Possible damages:, mucosal irritations LD50 Dermal - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 402) **Skin corrosion/irritation**

Skin - Rabbit

Result: Irritations - 4 h (OECD Test Guideline 404)

Remarks: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to

degreasing properties of the product. Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation Remarks: (ECHA)

Remarks: Risk of corneal clouding. **Respiratory or skin sensitization**

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: In vivo micronucleus test

Species: Mouse

Cell type: Bone marrow Application Route: Oral

Method: OECD Test Guideline 474

Result: negative **Carcinogenicity**

Limited evidence of carcinogenicity in animal studies

Suspected human carcinogens

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Methyl ethyl Ketone

Acute toxicity

LD50 Oral - Rat - male and female - 2,193 mg/kg

(OECD Test Guideline 423)

LC50 Inhalation - Mouse - 4 h - 32,000 mg/m3 - vapor

Remarks: (RTECS)

LD50 Dermal - Rabbit - 6,480 mg/kg

Remarks: (RTECS)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Severe irritations (OECD Test Guideline 405)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: rat hepatocytes

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available **Aspiration hazard**

No data available

11.2 Additional Information
Endocrine disrupting properties

Methylene Chloride (75-09-2)

Assessment:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Repeated dose toxicity - Rat - male and female - Oral - 104 Weeks - NOAEL (No observed adverse effect level) - 6 mg/kg Repeated dose toxicity - Rat - male and female – Inhalatio 104 Weeks RTECS: PA8050000 Dizziness, Nausea, Vomiting, narcosis, Cough, irritant effects, Unconsciousness, Shortness of breath, respiratory paralysis, somnolence, depressed respiration, CNS disorders, inebriation' Risk of corneal clouding . The following applies to aliphatic halogenated hydrocarbons in general: systemic effect: narcosis, cardiovascular disorders. Toxic effect on liver, kidneys. Dichloromethane is metabolized in the body producing carbon monoxide which increases and sustains carboxyhemoglobin levels in the blood, reducing the oxygen-carrying capacity of the blood.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Methyl ethyl Ketone

Assessment:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Central nervous system depression, Gastrointestinal disturbance, narcosis

To the best of our knowledge, the chemical, physical, and toxicological properties have not

been thoroughly investigated.

Liver - Irregularities - Based on Human Evidenc

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity Ecotoxicity

Methylene Chloride

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

193.00 mg/l - 96 h

Remarks: (ECHA) Toxicity to daphnia and other aquatic invertebrates

static test LC50 Daphnia magna (Water flea) - 27 mg/l - 48 h

(US-EPA)

Toxicity to bacteria static test EC50 –

(OECD Test Guideline 209)
Toxicity to fish(Chronic toxicity)

flow-through test LC50 Pimephales promelas (fathead minnow) - 471 mg/l - 8 d

Remarks: (ECHA

Methyl ethyl Ketone

Activated sludge 2,590 mg/l - 40 min

Toxicity to fish static test LC50 - Pimephales promelas (fathead minnow) - 2,993

mg/I - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

static test EC50 Daphnia magna (Water flea) - 308 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 Pseudokirchneriella subcapitata - 1,972 mg/l - 72 h

(OECD Test Guideline 201)

12.2 Persistence and degradability

Methylene Chloride aerobic - Exposure time 28 d Result: 68 % - Readily biodegradable. (OECD

Test Guideline 301D)

Methyl ethyl Ketone Biodegradability aerobic - Exposure time 28 d

Result: 98 % - Readily biodegradable.

(OECD Test Guideline 301D)

Theoretical oxygen demand# 2,440 mg/g

Remarks: (Lit.)

Ratio BOD/ThBOD 76 % Remarks: (IUCLID)

12.3 Bio accumulative potential

Methylene Chloride Cyprinus carpio (Carp) - 6 Weeks - 250 μg/l(Dichloromethane)

Bioconcentration factor (BCF): 2 - 5.4 (OECD Test Guideline 305) Cyprinus carpio (Carp) - 6 Weeks - $25 \mu g/I$ (Dichloromethane) Bioconcentration factor (BCF): 6 - 40 (OECD Test Guideline 305)

Methyl ethyl Ketone No data available

12.4 Mobility in soil

Methylene Chloride No data available Methyl ethyl Ketone No data available

12.5 Results of PBT and vPvB Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission. Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1 UN Number

 UN No (ADR/RID/ADN)
 1950

 UN No (IMDG)
 1950

 UN NO (ICAO)
 1950

14.2 UN Proper Shipping Name

ADR/IMDG/AND/RID AEROSOLS

IATA Aerosols Flammable

14.3 Transport Hazard Class(es)

ADR/RID/ADN Class 2.1

ADR/RID/ADN Class Class 2: Gases ADR Label No 2.1 & 6.1 IATA 2.1 **IMDG Class** 2.1 ICAO Class/Division 2.1 **ICAO Subsidiary Risk** 6.1 **ICAO TEC* No** 20GSF Air Class 2.1 **UK Road Class** 2.1 **Transport Labels** L.Q.



14.4 Packing Group

Not Applicable

14.5 Environmental Hazards

Dangerous for the environment No Marine pollutant No

Other information No supplementary information available

14.6 Special Precautions for user

Overland Transport

Classification Code (ADR): 5F

Special Provisions (ADR): 190,327,344,625

Limited Quantities (ADR): 11 Excepted Quantities (ADR): E0

Packing Instructions (ADR): P207,LP02
Special Packing provisions (ADR): PP87, RR6, L2

Mixed Packing provisions (ADR): MP9
Transport Strategy (ADR): 2
Special provisions for carriage – Packages (ADT) V14

bond-X Ltd REV 5.0 JULY 2024

Special Provisions for carriage – Loading, unloading

and handling (ADR): CV9, CV12

Special provisions for carriage – Operation (ADR): S2
Tunnel Restriction Code: D

Transport by Sea

Special Provisions (IMDG): 63,190,277,327,344,959

Limited Quantities (IMDG): SP277 Excepted Quantities (IMDG): E0 Packing Instructions (IMDG): P207,LP02 Special Packing provisions (IMDG): PP87,L2 EmS-No (Fire): F-D EmS-No (Spillage): S-U Stowage category (IMDG): None Stowage and Handling (IMDG): SW1,SW22 Segregation (IMDG): SG69 MFAG-No: 126

Air Transport

PCA Excepted Quantities (IATA): E0
PCA Limited Quantities (IATA): Y203
PCA Limited Quantity max net quantity (IATA): 30KgG
PCA Packing instructions (IATA): 203
PCA max net quantity (IATA): 75Kg
CAO packing instructions (IATA): 203
CAO max net quantity (IATA): 150Kg

Special provisions (IATA): A145,A167,A802

ERG Code (IATA): 10L

Inland Waterway Transport

Classification Code (ADN): 5F

Special Provisions (ADN): 190,327,344,625

Limited Quantities (ADN):

Excepted Quantities (ADN):

Equipment required (ADN):

Ventilation (ADN):

VE01,VE04

Number of blue cones/lights (ADN): 1

Rail Transport

Classification Code (RID): 5F

Special Provisions (RID): 190,327,344,625

Limited Quantities (RID): 1L Excepted Quantities (RID): E0

Packing Instructions (RID): P207,LP02
Special Packing provisions (RID): PP87,RR6,L2

Mixed Packing provisions (RID): MP9
Transport Category (RID): 2
Special Provisions for carriage – Packages (RID): W14

Special Provisions for carriage – Loading, unloading

and handling (RID): CW9, CW12

Colis Express (express parcels) (RID): CE2
Hazard Identification No (RID): 23

14.7 Transport in bulk according to Annex II of MARPOL and the IBC code

Not applicable

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Labelling according to Regulation (EC) No 1272/2008

The chemicals (Hazard information and packaging for supply) regulations 2009 (S.I 2009 No. 716). Control of substances hazardous to health.

Approved code of practice.

Guidance notes

Workplace exposure limits EH40.

15.1.1 EU-Regulations

Contains no REACH substances with Annex XVII restrictions.

Contains no REACH Annex XIV substances.

15.1.2 National Regulations

No additional information available.

SECTION 16: OTHER INFORMATION

General information

This product should be used as directed. For further information consult the product data sheet or contact technical services.

Information sources

This safety data sheet was compiled using current safety information supplied by distributor raw materials.

Revision comments

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact AFT Aerosols Ltd.

Hazard statements in full

H220	Extremely flammable gas
H222	Extremely flammable aerosol.
H351	Suspected of causing cancer
H315	Causes skin irritation.
H310	Causes serious eye irritation.
H336	May cause drowsiness or dizziness

Abbreviations

Carc 2	Carcinogen Category 2
Skin Irrit 2	Skin Irritant Category 2
Eye Irritant 2	Eye Irritant Category 2

STOT SE 3 Specific Target Organ Toxicity Single Exposure Category 3

Carc Cat 3 Carcinogen Category 3 Flam Gas 1 Flammable Gas Category 1

ISSUE: REV 5.0

LAST REVIEWED: JULY 2024

DISCLAIMER

The Information provided herein, especially recommendations for the usage and the application of this products, is provided in good faith, and no liability on the part of bond-X Ltd is stated or implied. No employee of bond-X Ltd has the authority to waive or alter in any way the content of this document.

Due to different materials used, as well as to varying working conditions, production techniques, and the requirements of the end users, all of which are beyond our control, we strongly recommend that thorough and extensive trials are carried out in order to test the suitability of our products with regard to the required processes and applications. This should also include an ageing test which should be applied to all substrates used.

It is also the responsibility of the purchaser and end user of this product to ensure that all appropriate actions necessary for the protection of the environment, and for the health and safety of their employees are observed.

This datasheet replaces all former versions